



NATIONAL INSTITUTE OF UNANI MEDICINE

Kottigepalya, Magadi Main Road, Bangalore – 560 091.

(An autonomous body under Govt. of India, Ministry of AYUSH)

Tel : 080-23584260

Fax: 080 -23584180

F.No.04-03/2016-17/NIUM/Admn./Vol.III/ 1598

Date.06 /11/2017.

To,

Subject: Invitation of quotation for supply of Instruments/ Items for Post Operative Observational Room: – reg.

Sir,

With reference to the subject mentioned above, Quotations are invited from reputed registered dealers for the supply of Hospital items as detailed below.

Sl. No	Name of the Items	Specification /Make	Quantity Required.	Amount (`)	Total GST Amount (`)	Grant Total (`)
01	Motorized Bed	<ul style="list-style-type: none">➤ EX6000 Plus (Fully Motorized) 5 Section PP Tops, 125mm Twin Wheel Castors. Central Locking Mech., Rubber Buffers at 4 corners Handset, ACP Box, Battery Back up, SMPS Bed Extension, Linen Holder, Night Lamp, Angle Indicator 0185 Polymer Moulded Head and Foot Panels (Removable) 0360 Polymer Moulded Split Safety Rails (2 sets) 0156 Urine Bag Holder (Single) + 0164 S.S Heavy Duty I.V Pole (2 hooks).➤ Premium mattress with wave shape on both sides High quality, high density flame retardant foam and cover fabric having flame retardant, anti bacterial, anti skid properties.	02 No's			

02	Ventilator	<ul style="list-style-type: none"> ➤ Infant to Adult ICU Ventilator with Advanced Compressor design. ➤ Volume and pressure controlled Breath types. ➤ Invasive and Non Invasive applications as standard. ➤ Inline Nebulizer backup. ➤ 4 hours battery backup. <p>Modes: SIMV-PC+PS SIMV-PC+PS A/CMV-PC A/CMV-PC CPAP-PC CPAP-PC NIV-PC</p>	01 No's			
03	Monitor	<ul style="list-style-type: none"> ➤ 6 channel Multipara monitor with 10.4" High resolution LED display. ➤ Basic configuration: ECG, Respiration, Dual temperature, NiBP, SpO2. ➤ Optional parameters: Dual IBP (internal/external) ➤ Microstream EtCO2. ➤ Advanced features like Sat Seconds, LoSat, IPI etc. ➤ ST segment analysis & Arrhythmia analysis. 	02 No's			
04	Defibrillator	<ul style="list-style-type: none"> ➤ Bi-phasic defibrillator with synchronised Cardio version. ➤ IJ-300J 19 steps ➤ Charges to 300j from fully charged battery. ➤ 6.5"Color TFT LED Display. ➤ Adult/Paediatric paddles. 	01 No's			
05	ECG Machine	<ul style="list-style-type: none"> ➤ ECG Machine with Display ➤ 12 Lead High speed acquisition at 1000 samples/sec/channel ➤ High resolution 3 channel Thermal printer. ➤ Formated, Standard and 	01 No's			

		Carbera Formates.				
06	Dressing Trolley with Bowl and Busckt	<ul style="list-style-type: none"> ➤ Size L- 1080 X B 460mm X 830mm SS Shelves with railing top SS bowl diameter 345mm, Bucket diameter 300mm, epoxy powder coated frame with SS shelves and railing, 	02 No's			
07	Electric suction machine	<ul style="list-style-type: none"> ➤ Steel, Epoxy powder Coated, Fitted with Oil immersed motorised vacuum pump with 2 Graduated Glass suction jars, each of 1.6 litres capacity with synthetic Rubber Lids, Long Pressure Tubing, Vacuum Control, Automatic overflow cut-off device mounted on 2 rubber wheels. 	01 No's			
08	Emergency medicine trolley	720x650x600 mm, 6 drawer, modular system, upper 2 drawers with medicine container, 6 plastic bins, top tray for monitor and pulse oxymeter 100mm diameter wheels with pair of front brakes, Epoxy finish.	01 No's			
09	IV drip stand	<ul style="list-style-type: none"> ➤ Mobiles IV Drip stand powder coated solid steel base with stainless steel, Tubular legs. 	02 No's			
10	Oxygen cylinder	<ul style="list-style-type: none"> ➤ B type 10ltr 	04 No's			
11	Oxygen cylinder trolley	<ul style="list-style-type: none"> ➤ Pull type with 3 wheels of 50mm Diameter, Metallic with wheels with all attachments. 	02 No's			
12	Oxygen cylinder with stand	<ul style="list-style-type: none"> ➤ Oxygen cylinder should be B type 10.5 ltrs type 2. Should be supplied with humidifier and flow meter, Vacuum insulated cryogenic storage tanks have the following features: Stainless steel welded body and tank. Stabilising pressure safety valves, Multiple layer insulation system, Used in storage and transportation of liquefied air gas 	02 No's			

		product (lo2,In2,lar), Vacuum by advanced high diffusion pump, Advanced helium mass spectrum technique for checking vacuum, Inner tank of stainless steel with pull type trolley having 3 wheels of 50 mm diameter.				
13	AC	<p>➤ 2 Ton Split AC, 7150 Watts of cooling capacity.</p> <p>Design: The sleek and stylish, 2 Ton Split AC comprises of an indoor unit having 320x998x238 (H x W x D) mm dimensions and 13kg weight and an outdoor unit having 650x830x320(H x W x D) mm dimension and 55kg weight. Hydrophilic coated heat exchangers ensure corrosion resistance for longer life. There is a large fan with powerful motor for better heat transfer.</p> <p>Speed of cooling: Housed in large outdoor unit, 2 Ton Split AC carries high BTU hyper tropical compressors with large copper heat exchanger which provides quick and efficient cooling.</p> <p>Sleep Mode and Timer: The sleep timer and program timer function not only allow you to enjoy an uninterrupted sleep but also save energy.</p> <p>Noise Level: 2 Ton Split AC has 35 dB indoor noise level.</p> <p>Technology: 2 Ton Split AC features three-dimensional air flow technology which ensures proper wind direction control. This air flow control makes your environment more comfortable with both vertical and horizontal direction at the same time automatically.</p> <p>Any Other Specs: Other additional features of include up/down swing flaps, Auto Restart, Power air flow dual flaps, powerful mode,</p>	01 No's			

	<p>BLDC motor indoor unit, inner groove copper tube, wide angle louver, dry function, automatic airflow adjustment, economy mode and wireless remote controller.</p> <p><u>Energy Ratings:</u> BEE 2 star energy rating.</p> <p>Capacity : 2 Ton(s) BEE Rating : 2 Star AC Type : Split Features : Automatic Air Flow adjustment, Dry Rotary Compressor Noise Level Indoor : 35 DB Timers : Yes Auto Restart : Yes Sleep Mode : Yes Remote Control : Yes Air Swing : Yes Color : White Dimension : 998x238x320 Weight : 13</p>				
--	---	--	--	--	--

The quotations may be submitted in a sealed cover quoting the competitive rate with specification by clearly mentioning taxes applicable if any., time required for supplying the items with the terms & conditions, Copy of GST Certificate may kindly be enclosed.

The envelope containing quotation should be super scribed as **“Quotation for supply of Instruments/ Items for Post Operative Observational Room”**

The last date for the submission of quotation is: **21/11/2017.**

Yours faithfully,

Sd/-
(Suresha)
Accounts Officer

Distribution :

- 1.Dr.S.Shah Alam, HoD, Dept. of Jarahiyat, for information.
- 2.Website in-charge for information and to upload quotation in NIUM- website.
- 3.Concern file.
- 4.Guard file.